SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: The Wood Stain, Oil-Based Wood Stain

IDENTIFICATION NUMBER: LT-08-145

COMPANY: WW CO. LLC

SIZES: 32 OZ, 128 OZ, 640 OZ

DISTRIBUTOR: WW Co. LLC. 1299 W 635 S Orem, UT 84058

CHEMICAL INFORMATION: Support@TheWoodStain.com

CHEMTREC 24HR EMERGENCY TELEPHONE 800-424-9300

SECTION 2 - HAZARDS IDENTIFICATION

*** EMERGENCY OVERVIEW ***: Harmful if swallowed or inhaled. On overexposure, could cause (target organ or system) damage. (e.g., lung, nervous system, blood disorders, liver, kidney, immune system, cardiovascular system, thyroid, testicular, ovarian, etc.).

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - INHALATION: Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor or skin exposure. Prolonged inhalation may be harmful.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed.

GHS CLASSIFICATION

Flammable liquids : Category 3
Skin irritation : Category 3
Specific target organ toxicity – single exposure: Category 3 Central Nervous Sys
Aspiration hazard : Category 1

GHS Label element

Signal word	:	Danger
Hazard statements		H226 Flammable liquid and vapor. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness.
Precautionary statements **Prevention:**	:	P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

CAS-No.	Components	Weight Percent
64741-65-7	Odorless Mineral Spirits	50-75%
66455-33-2	Alkyd Resin	15-25%
64742-88-7	Medium Aliphatic Solvent Naphtha	1.0-2.5%

	EXPOSURE LIMITS					
	ACGIH		OSHA		COMPANY	
ITEM	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN
01	100	100	100			NO
02	N.E.	N.E.	N.E.	N.E.	N.E.	NO
03	N.E.	N.E.	N.E.	N.E.	100ppm	NO
04	100 ppm	150 ppm	100 ppm	N.E.	100 ppm	NO
05	N.E.	N.E.	N.E.	N.E.	N.E.	NO

(See Section 16 for abbreviation legend)

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and shoes. Do not reuse until cleaned.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 129 F

LOWER EXPLOSIVE LIMIT: 1.0 %
UPPER EXPLOSIVE LIMIT: 6.6 %

AUTOIGNITION TEMPERATURE:

SECTION 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Ventilate area. Absorb spill with suitable absorbent material, then place in a chemical waste container. If large spill, dike area and call spill response team. Notify appropriate state and local agencies.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Wash thoroughly after handling.

STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use. Do not weld, heat or drill on or near container; even emptied containers can contain explosive vapors. Store away from strong oxidizing agents in a cool, dry place with appropriate ventilation.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment.

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace

SECTION 11 - TOXICOLOGICAL PROPERTIES

TOXICOLOGICAL INFORMATION: No Information.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Refer to local, county, state and federal storm water and air quality regulations.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: If discarded, this material and its containers may have to be treated as hazardous waste based on the characteristics of ignitability as defined under Federal RCRA regulations (40 CFR 261). Disposal of this material may require compliance with applicable labeling, packaging, and record keeping standards. Extreme care should be taken to ensure that it is disposed of only in a facility permitted for disposal of hazardous waste.

SECTION 14 - TRANSPORTATION INFORMATION

Special Notes: The flash point for this material is greater than 100 F (38 C). Therefore, in accordance with 49 CFR 173.150(f) non-bulk containers (<450L or <119 gallon capacity) of this material may be shipped as non-regulated when transported solely by land, as long as the material is not a hazardous waste, a marine pollutant, or specifically listed as a hazardous substance.

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:
This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD

SARA SECTION 313:
This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

---------- CHEMICAL NAME ----------	CAS NUMBER	WT/WT % IS LESS THAN

No product or component toxicological information is available.

SECTION 15 - REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65:
WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 10/2/2023

VOLATILE ORGANIC COMPOUNDS (VOCS): .768 lbs/gal, 92.16 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined